

★ HITA U11 95-120103/16 ★ JP07045489-A
 Semiconductor manufacturing system . incorporates network
 adaptor to connect driver receiver for RS232-C and parallel
 input = output port to semiconductor manufacturing apparatus with
 or without communication junction

HITACHI LTD 93.08.02 93JP-209898

(95.02.14) H01L 21/02


Addn. Data: AKITA DENSHI KK (AKIT.)

The semiconductor manufacturing system is constituted by an RS485
 interface. A transceiver for RS485 interface is connected to a
 network adapter which connects various kinds of semiconductor
 devices (DICE, BNDE, MLDE, AGE, AHE, AHNE) to a host computer
 (HOST). A driver receiver for a RS232C is connected to the
 semiconductor manufacturing apparatus which has a
 communication junction by SECS protocol or by a peculiar
 communication protocol. The network adapter connects the PIOP to
 the semiconductor manufacturing apparatus which does not have a
 communication junction.

ADVANTAGE - Avoids need for large hardware reconstruction
 and software change. Reduces time and cost required for
 development. (6pp Dwg.No.1/3)

N95-084587

U11-C15B



©1995 DERWENT INFORMATION LIMITED

Derwent House 14 Great Queen Street London WC2B 5DF England UK

Derwent Incorporated

1420 Spring Hill Road Suite 525 McLean VA 22102 USA

Unauthorised copying of this abstract not permitted



DERWENT

Scientific and Patent Information